

Engine Protection

The robust frame with side covers protects the rubber-mounted engine from external forces.


Easy to Service

Engine is easy to service with simple access to all the service points

Low Fuel Consumption

The built-in fuel tank provides hours of uninterrupted work.

Efficient & Durable











Specs	RD36	RD37D	
Operating mass	28 kg	59 kg	
Manufacturer/Model	Honda Engine GX160	Greaves 1520	
Туре	Petrol	Diesel	
Power	3.6kW @ 3,600 rpm	3.67kW @ 3,600 rpm	
Fuel tank capacity	3.1 Liters	4.1 Liters	

Specs	RD22E	
Operating mass	28 kg	
Manufacturer/Model	Branded	
Туре	Electrical single phase	
Power	2.2kW @ 2,800 rpm	
Voltage	230 V, AC	

REDLINE Pokers with 30mm, 45mm and 60mm Tube Head Diameter

Specs	RP30	RP45	RP60
Centrifugal force, kN	4.5	4.5	5.8
Poker Type	Pendulam	Pendulam	Pendulam
Noise Level, dB	80 - 85	78	83
Frequency, vpm	12500	12000	11300
Tube Head Diameter, mm	30	45	60
Hose Length, m	5	5	5
Weight, kg	14.5	16	18
weight, kg	14.5	10	10









